

Polo Shirt

822

Xispal RS

Features:


- Comfort, breathable
- Piqué weave
- Inherent performance
- Weight: 220g/m²

Composition:

- 50% Cotton
- 39% Acrylic Modified Type-F
- 10% Viscose
- 1% Antistatic

Sewing thread: 100% M-Aramid

CERTIFICATE BY NOTIFIED ORGANIZATION NO0162



A/CHEST	HEIGHT	A/WAIST	S
100 - 104 cm	168 cm	98 - 102 cm	S
104 - 108 cm	174 cm	102 - 106 cm	M
108 - 112 cm	180 cm	106 - 110 cm	L
112 - 116 cm	186 cm	110 - 114 cm	XL
116 - 120 cm	192 cm	114 - 118 cm	XXL

EN Protective garments for workers exposed to heat and flame, electrostatic charges, and the thermal risks of an electric arc.

ES Ropa de protección para trabajadores expuestos al calor, con propagación limitada de llama, cargas electrostáticas y riesgo de arco eléctrico.

FR Vêtements de protection pour les travailleurs exposés à la chaleur, la flamme, charges électrostatiques et risque d'arc électrique.

IT Indumenti di protezione per utenti esposti al calore, con limitata propagazione della fiamma, cariche elettrostatiche e rischio di arco elettrico.

DE Schutzkleidung für wärmeexponierte arbeiter mit begrenzter flammenausbreitung, elektrostatischer ableitung und gegen thermischen gefahren des störlichtbogens.

Polo Shirt 822 XISPAL RS



TEST / EXPERIMENT
Flame Spread
Index 3
PASS
CLASSIFICATION

TEST / EXPERIMENT
Burs strength
>00 kPa
PASS
CLASSIFICATION

TEST / EXPERIMENT
Electric arc (4hA)
PASS
CLASSIFICATION

TEST / EXPERIMENT
Charge Decay
t_{1/2} > 0.1 s
t_{1/2} > 45
NA
CLASSIFICATION

TEST / EXPERIMENT
Surge Resistivity
5 < 0.2
NA
CLASSIFICATION

TEST / EXPERIMENT
Gap between conductor yarns
≤ 10 mm
NA
CLASSIFICATION

EN 1149-5/08

Behavior with flame (minimum level: A)

Convective heat (minimum level: B)

Radiant heat (minimum level: C)

Contact heat (minimum level: F)

EN ISO 1612/15

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

AI BI CI

II. INFORMAZIONI E ISTRUZIONI PER L'USO

Fabri di Humidita

STORAGE Stocked dans le container d'origine, à

TEMPERATURE 15°C - 25°C

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

III. INFORMAZIONI E ISTRUZIONI PER L'USO

Fabri de Humiditat

STORAGE Stocked dans le container d'origine, à

TEMPERATURE 15°C - 25°C

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

IV. INFORMAZIONI E ISTRUZIONI PER L'USO

Fabri de Humiditat

STORAGE Stocked dans le container d'origine, à

TEMPERATURE 15°C - 25°C

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

V. INFORMAZIONI E ISTRUZIONI PER L'USO

Fabri de Humiditat

STORAGE Stocked dans le container d'origine, à

TEMPERATURE 15°C - 25°C

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

REPAIRS REPAIRS

VI. INFORMAZIONI E ISTRUZIONI PER L'USO

Fabri de Humiditat

STORAGE Stocked dans le container d'origine, à

TEMPERATURE 15°C - 25°C

REPAIRS REPAIRS

REPAIRS REPAIRS